

BEVERLY HILLS FIRE DEPARTMENT FIRE PREVENTION BUREAU REQUIREMENTS USE OF CAMERA/JIB/BOOM/CRANE IN PUBLIC ASSEMBLAGES

Event Name	
Event Date/Time: _	
Event Location:	

- 1. May require uniform Fire Safety Officer when camera jib/boom/crane is used within the audiences area of a public assemblage.
- 2. Any portion of the camera jib/crane/boom that extends over the audience shall be a minimum of 8 feet in height above the ground/floor/grade.
- 3. At no time shall the base of the jib/crane/boom block an exit or aisle.
- 4. A device shall be provided to prevent the dolly's movement into a restricted area.
- 5. Cables shall be taped, matted, or flown to avoid tripping hazards.
- 6. Minimum clearance around the base and/or operator shall be four feet. Barricades or rope and stanchions shall be provided to maintain this clearance.
- 7. Request for approval shall be submitted in writing, with plans drawn to scale **at least 3 working days** in advance of the event.
- 8. Camera must be safety cabled to the jib/crane/boom.
- 9. If used in the dark, low wattage illumination will be required on both sides of the jib/crane/boom attached to the camera.
- 10. Visibility of exit signs shall not be hindered.
- 11. Any portion of the jib/crane/boom or camera that may come into contact with the public shall be padded.
- 12. Use of a safety person may be required, in addition to the camera operator.
- 13. Comply with Beverly Hills Fire Department requirements.

Name of Company

Telephone #

Address of Company

Signature

Date